

EUROPA
ANTI-THEFT ENGINEERING



HEXABOLT
6 TIMES STRONGER

Our Mission : "ANTI-THEFT ENGINEERING"
Our Vision : "We shall be a Global Provider of customized anti-theft products + solutions for every house + institution, with an "Idea to Actual theft prevention" value chain, having a global mind set; being a good place to work, learn and grow; with a culture of disruptive innovation and continual improvement."

The EUROPA journey began in the year 1984 with the Mission "ANTI-THEFT ENGINEERING". Dr. P. A. Joshi after studying in Germany (Dr. Ing : Doctorate in Mechanical Engineering & B. E. [Mechanical]), founded this Company in the Cultural and Industrial city of Pune. Since then, Welmade Locking Systems Private Limited has carved for itself an enviable niche in the Indian Market. Continuous growth based on innovative Product Engineering and Strategic thinking has made the Company the Brand Leader, giving the EUROPA Brand its excellent reputation.

Backed by world-class technology and driven by a dedicated team of over 400 dynamic professionals (25% are involved in Design & Development), the company manufactures international standard products which have been appreciated in trade fairs like the KOLN TRADE FAIR held in Germany.

We constantly INNOVATE to design and manufacture locks with best-in-class features meeting Global function, finish, load (strength) & life (warranty) standards.

We have applied for and received a large number of Patent and Design Registration.

Dr. P. A. Joshi, founder of the Company, was requested to provide services as the International Consultant for 'Global Mapping of Lock Technology' by UNIDO (United Nations Industrial Development Organization), Vienna, Austria in 2003. He was deputed by UNIDO to visit and study over 25 Lock Factories in Germany, Switzerland, Spain, France, UK, Italy, Hongkong, China & Taiwan.

We have a wide network of Sales branches across India, Manufacturing units in Bhosari & Chakan (Pune) and Head Office in Bhosari, Pune.

Europa has been awarded the "G. S. Parkhe Industrial Merit Award" in the year 1990, and the "Hari Malini Joshi Award" in the year 1995, by MCCIA, PUNE for outstanding Product Design.

In the year 2015, Dr. P. A. Joshi the Chairman of the company was awarded the "Excellence in First Generation Entrepreneurship Award" by Entrepreneurs' International club of Pune.

EUROPA
ANTI-THEFT ENGINEERING

COMPANY PROFILE

EUROPA PRODUCT RANGE



EUROPA
ANTI-THEFT ENGINEERING

COMPANY PROFILE

PRODUCT WARRANTY

EUROPA
ANTI-THEFT ENGINEERING

THIS PRODUCT OFFERED BY **WELMADE LOCKING SYSTEMS PRIVATE LIMITED**, IS WARRANTED TO BE FREE FROM MECHANICAL DEFECTS FOR A PERIOD OF 15 YEARS FROM THE DATE OF PURCHASING MENTIONED ON THE PRODUCT. DAMAGE DUE TO ABUSE OR NEGLIGENCE, FAULTY INSTALLATION/FITMENT IS NOT COVERED IN WARRANTY. IN DUE COURSE OF TIME OF WARRANTY IF PRODUCT IS FOUND TO BE DEFECTIVE IN WORKMANSHIP OR DUE TO ANY MATERIAL/PARTS TO BE USED, PRODUCT WILL BE REPAIRED OR REPLACED BY SIMILAR PART / PRODUCT AT SOLE DISCRETION OF THE COMPANY.

WARRANTY TERMS AND CONDITIONS

- Product offered by 'EUROPA', comes with warranty, for a period of 15 years from the date of Purchasing.
- If product undergoes repair or replacement, product warranty will be effective from the original date of purchase. The original warranty card should be submitted with the defective product in case of replacement. The warranty card with the new product should be filled with original date of purchase. Company will own faulty parts / product Defective parts / product should be returned to company.
- Product damage or non-operation of the product due to sagging of door i.e. hinge loosening, or due to weather effect on product or door frame are not covered under this warranty.
- Product surface finish and shade variation is not covered under this warranty.
- Any modification, tampering or amendment in the warranty card or purchase bill/invoice will void the warranty of product.
- Product warranty will be void in following circumstances or conditions:
 - Mishandling / improper installation / misuse / improper application.
 - Not following direction / instruction of use.
 - Failure to install product without using installation guide.
 - Modification to the product / part or removal / alteration of parts and components.
 - Application or seepage of liquid / oil / chemical into key hole or inner part of product.
 - Product damage or non functional due to improper operational environment, such as natural calamity, lightning, exposure to direct sunlight, rain, high humidity etc.

WARRANTY

- In case a product found non-operational after purchase and before installation then same will be replaced after confirmation at point of sale.
- Product to be installed / repaired by 'EUROPA' authorized technician, if not then warranty claim will be void.
- All incidental charges in the course of repair / rectification shall be borne by the consumer / purchaser.
- Liability of / for any consequential loss or damage is neither accepted nor implied and is expressly excluded from warranty.
- Warranty carries maximum liability limited to the cost of the product and not valid outside India.
- To avail this warranty, customer should produce this warranty card, duly filled, along with original purchase bill or invoice to the nearest 'EUROPA' dealer, distributor.
- Company holds right to amend the design/shape/colour of the product without prior notice, in accordance with Company's continual technical improvement process.
- 'Welmade Locking Systems Private Limited', will have Final Decision on warranty claim and will be binding.
- Matters / claim arising under this warranty will be subject to Pune jurisdiction only.

48 HOUR SPARE KEY SERVICE

Company will arrange to manufacture duplicate spare keys within 48 working hours from the date/time of receipt of following essentials in the factory premises by post/courier/e-mail:

- Scan copy or photocopy of top & side view of the key with key number clearly visible
- Mention name/address/Contact No./Qty of Keys required
- Add address proof-photocopy (electricity bill/driving license/passport/voter id card)
- Identity proof-photocopy (pan card/driving license/Aadhar card/voter id card)

 (This time span of 48 hours does not include the time taken for this card to reach the company and the time taken for the key to reach the customer after keys leave the company. It excludes the weekly offs, festivals & national holidays as well as delays due to power cuts, the material / tool shortage, labour unrest, m/c breakdowns, lockdowns, viral pandemic issues and other delays normally likely to be observed in factory.) The keys will be sent by Courier on 'to pay' basis. After the payment of charges to company's bank account. For further details please contact service@europalocks.com

WARRANTY

PLEASE FILL IN DETAILS BELOW & KEEP WARRANTY CARD SAFELY

KEY No. :

EUROPA
ANTI-THEFT ENGINEERING

Name : _____
Address : _____
Contact : _____
E-mail : _____
Date of Purchase : _____
Invoice No. : _____ Invoice Date : _____
Product Code : _____
Name & Address of Dealer : _____
Contact No. of Carpenter : _____

CONTACT DETAILS :
WELMADE LOCKING SYSTEMS PRIVATE LIMITED
J-61, MIDC, BHOSARI, PUNE - 411026, MAHARASHTRA (INDIA).
TEL. : 020-27125012, EMAIL : service@europalocks.com
VISIT US : www.europalocks.com

NOTE: KINDLY PRESERVE THIS CARD CAREFULLY DURING RENOVATION (PAINTING/CONSTRUCTION WORK) COVER KEY HOLE OR CYLINDER BY ADHESIVE TAPE TO AVOID ENTRY OF DUST FOREIGN PARTICLES INTO IT. DO NOT USE OIL IN LOCK ASSEMBLY FOR CLEANING. USE OUR RECOMMENDED PRODUCT 'ZORRIK 88' WD40/MUSTLOCK 631.

DIMPLE KEY REGISTRATION CARD

To obtain spare duplicate keys, kindly fill in and send this card to the company, spare keys can not be supplied to you without this card

Key No. : _____
(attach clear xerox of both side of key)
Customer Name : _____

Address (Address to which keys are to be sent) : _____

Quantity of spare keys required _____ Nos.

Date _____ Signature _____

WARRANTY

REGISTRATION

1st time in INDIA
EUROPA
Presents
ANTI-BURGLARY INSURANCE
Worth Rs. 3 Lakhs



HEXABOLT
6 TIMES STRONGER

EUROPA
ANTI-THEFT ENGINEERING

INSURANCE

ANTI-BURGLARY INSURANCE(ABI) PROSPECTUS

Dear Customer,
We would like to compliment you on choosing of EUROPA and welcome you to the family of satisfied customers. With EUROPA, you get the best technology available today backed by the assurance of quality performance for years to come. You will discover the exact meaning of security the day you install EUROPA locks on your door. In keeping with our Global philosophy of total customer satisfaction, we offer you Anti Burglary Insurance risk cover (absolutely Free) from United India Insurance Company Limited, for a period of 12 months. In your interest, Please Scan QR Code tagged with KEYS and do register digitally for Anti Burglary Insurance by uploading needful details & documents through Anti-Burglary Insurance Registration Form to avail the ABI.

ANTI BURGLARY INSURANCE
Get free Anti-Burglary Insurance Worth ₹. 50,000/- with DPL P370BI & worth ₹. 2,00,000/- with Center Shutter Lock (S310 BR, S320 BR, S310 SC & S320 SC) & worth ₹. 3,00,000/- with Europa Hexabolt Lock.

FILL THE "Registration Form" AS PER THE INSTRUCTIONS PROVIDED HERE AND GET 1 YEAR ANTI BURGLARY INSURANCE POLICY FROM UNITED INDIA INSURANCE COMPANY LIMITED FREE OF COST **. Registration form to be filled in ENGLISH ONLY and use of any other language will not be accepted.

In case of Burglary, kindly contact to United India Insurance Company Limited, Divisional Office, Above Rajendra Honda Showroom, 2nd Floor, Near Sahyadri College, Sangamner Nashik Road, Sangamner-422605, Contact No 9790702172, Email id-162900@uiic.co.in & tpsawarkar@uiic.co.in

ABI Claim Intimation Form – In Case of burglary, kindly download this form available on our website in Services section under "Anti Burglary Insurance" and send to the above-mentioned insurance company along with the details as stated in Insurance prospectus.

ABI Registration Form - Scan the QR Code tagged with KEYS to fill the Form and submit online within 7 days from date of purchase of lock & in case of Flat/New House Possession (Builder Installed Lock) this limit is 30 days.

**Conditions apply as per Prospectus. Postage for claims to be borne by the customer.

EUROPA
ANTI-THEFT ENGINEERING

INSURANCE

SALIENT FEATURES OF THE POLICY: This is an extract of the Prospectus of the Policy. The complete Prospectus is available for Public reading at the Divisional Offices of United India Insurance Company Limited. Divisional Office, Above Rajendra Honda Showroom, 2nd Floor, Near Sahyadri College, Sangamner Nashik Road, Sangamner-422605. Applicable Insurance Company will indemnify loss for burglary due to forced breakage of insured Lock. This coverage is applicable only for homes and residential premises. The Coverage is not applicable for Shops, Offices and Godowns. Use of Duplicate keys is not covered (This coverage is restricted to burglary in the event of the breaking of the insured locks during the policy period. Burglary by any other means will not be covered). Installation of Lock recommended to be done as per defined lock installation standards etc provided along with lock packaging/refer website as per applicability of lock to avail ABI. TAX Invoice/Possession Letter (as applicable) is a must to register for ABI & to avail benefits of ABI.

PERIOD OF INSURANCE : 1 year from the date of purchase of Lock/ Possession date of Flat/House and subject to registration of ABI within 7 days / 30 days as per applicable.

Maximum Claim Amount: The Policy covers claim of applicable valuables up to ₹. 50,000/- for DPL P370BI & ₹. 2,00,000/- for Europa Center Shutter Lock (S310 BR, S320 BR, S310 SC & S320 SC) & ₹. 3,00,000/- for every EUROPA Hexabolt Lock.

Items Covered Under Europa Center Shutter Lock (S310 BR, S320 BR, S310 SC & S320 SC) Insurance : Commercial goods i.e. stock, furniture, fixtures, office automation equipment with a maximum sublimit of ₹. 20,000/- per item up to ₹. 2,00,000/-.

Items Covered Under DPL P370BI Insurance : Household Goods i.e. TV, Camera, Computer, Electric & Electronic items with a maximum sublimit of ₹. 5,000/- per item up to ₹. 50,000/-.

Items covered under Hexabolt Lock insurance : House hold goods i.e. TV, Camera, Computer, Electric & Electronic items with a maximum sub limit of ₹. 20,000/- per item up to total of maximum ₹. 3,00,000/-.

EUROPA
ANTI-THEFT ENGINEERING

INSURANCE

Excluded Items Under DPLP370BI, Center Shutter Lock (S310 BR, S320 BR, S310 SC & S320 SC) & Hexabolt Lock Insurance : Cash, valuables/Jewellery, Curious Antiques, other works of art, paintings, watches and all the items not mentioned in covered items list.

CLAIM PROCEDURE: In case of Burglary of items covered under this insurance policy, you are advised to abide by taking following steps:
1. To lodge F.I.R. with Nearest Police Station.
2. To send F.I.R. copy along with insured broken lock, ABI Claim Intimation Form, Summary A from JMFC or final investigation report by police whichever is available first and purchase (Tax Invoice / Possession Letter) bill (by registered post) to the Divisional Office of appropriate insurance company.

PAYMENT OF CLAIM : Payment for admissible claims will be made in Indian Currency and through A/c Payee Cheque / Pay order / Demand draft after due processing and on receipt of duly signed Discharge Voucher from the Beneficiary. Such payment will be made within 15 days from the date of receiving the signed Discharge Voucher from the Beneficiary.

OTHER TERMS: This Policy is available to Indian citizens only. Claims under this policy shall have to be taken in India. This Policy shall benefit only those who fill up the ABI Registration form & Claim Intimation Form as per the INSTRUCTIONS provided. The Applicable Insurance Company reserves the right to reject any person from being covered under this Policy without assigning any reason. The details provided by the intended Beneficiary may be verified by The Applicable Insurance Company and failure on part of the Beneficiary to provide documents certifying the details will result in rejection of claim or cancellation of Beneficiary Certificate ab initio. Welmade Locking Systems Private Limited reserves right to withdraw the coverage without prior notice. Subject to Pune Jurisdiction.

EUROPA
ANTI-THEFT ENGINEERING

INSURANCE

EUROPA
ANTI-THEFT ENGINEERING
HEXABOLT

FEATURES

- **HEXABOLT LOCK** - THE STRONGEST DOOR LOCK FROM EUROPA TO SUIT 30 - 55 MM OF INSIDE OPENING OR OUTSIDE OPENING DOOR.
- **Hexabolt lock**, an extra strong high security door lock with 6 strong 25mm projected bolts gives maximum safety from crowbar attack.
- **3 Axis Dimple Key** gives assurance against key duplication, over 10 million combinations.
- **Lockable knob** gives peace at inside your home from strangers.
- **Special Antitheft Strengthening Plate** gives extreme strength to your wood door frame & preventing it from cracking during the crowbar attack.
- **Extra Strong Flanged Receptacle**, a challenge to crowbar attackers.
- **Special lock & receptacle** are needed for outside opening door.
- Suitable for inside opening doors (Left / Right side opening).

CONTENTS

FLAP, LOCK BODY, DEAD BOLT LATCH BOLT, LOCKABLE KNOB, DEAD LOCK KNOB, RECEPTACLE, KEYS, LOCK ASSEMBLY, COVER RING, FIXING PLATE, STRENGTHENING PLATE, LOCK & RECEPTACLE FIXING SCREW (4 Nos.), CYLINDER FIXING SCREW (2 Nos.), STRENGTHENING PLATE FIXING SCREW (2 Nos.), LOCK BODY & RECEPTACLE FLAP SIDE FIXING SCREW (8 Nos.), LOCK BODY & RECEPTACLE FLAP SIDE FIXING SCREW (4 Nos.)

INSTRUCTIONS MANUAL

*Plate Handle will be provided only for H347 & H348, H317, H318, H367, H368 & H357, H358 Models

EUROPA
ANTI-THEFT ENGINEERING

FOR PLATE HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

HEXABOLT LOCK LATCH BOLT
(MODEL - H347, H348, H317, H318, H357, H358 & H367, H368)

PREPARE THE DOOR

- 1) Confirm that door and frame surface are in same level

- 2) Place your HEXABOLT lock body on the inside panel of the door at your desired height. (39" height from the floor recommended)
- 3) Mark the outline of the flap on the side face of the door with pencil, Ref Fig. 1 (L) & Fig. 1 (R).

- 4) Make a 2mm deep recess of 158 x 21mm on the marked area.
- 5) Once the recess is made ensure that the flap of your HEXABOLT lock remains flush with the surface of the door edge. (check it by keeping your HEXABOLT lock in the recess).
- 6) Fold the marker along the dotted line and place the shorter side of the marker in the recess.
- 7) Mark the hole centres A, B, C, D & E on the door panel with a pointed punch, Ref Fig. 2(L) & Fig. 2(R)
- 8) Now remove the marker and make 2 holes of Ø2.5x15mm deep at 2 locations of "C".
- 9) Make a Hole of Ø30mm throughout with hole saw cutter for Lock Assembly fitment at location "A".

EUROPA
ANTI-THEFT ENGINEERING

FOR PLATE HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

- 10) Drill a through hole of ø17mm at location "D".
- 11) Make 7 holes of ø3.5x25mm deep from inside of the door at location "B".
- 12) Secure the fixing plate from inside the door with (ø7x20mm) wood screws.

PROCEDURE FOR FITTING OF PLATE HANDLE, LOCK ASSEMBLY

- 13) Drill 4 nos through holes of ø6mm at location "E".
- 14) Insert the lock assembly & Square Rod in plate handle and keep the handle at it's desired position on the door, ref Fig. 3.
- 15) Mark 8-10mm (max) on Notch strip and Square Rod from outer face of fixing plate. Ref. Fig. 4(a) & Fig. 4(b).
- 16) Insert screws 3/16"x2" in to lock assembly and measure its extra length.
- 17) Remove the screws 3/16"x2" and cut the extra length from marked bottom side.

EUROPA
ANTI-THEFT ENGINEERING

FOR PLATE HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

- 18) Cut the extra length of Notch strip Ref Fig. 4(c) & Square Rod Ref Fig. 4(d) with Bolt Cutter. (Note:- Follow the instructions over the Square Rod for Cutting Ref Fig. 4(e)).

- 19) Remove the burr over the screws of (3/16"x2"), Notch strip & Square Rod with hand file.
- 20) Fix the Plate Handle with help of 4 Nos. screws (MS) with washers from inside of the door.
- 21) Cover-up the screw head with the caps, provided along with the packet.
- 22) Fix the Lock Assembly along with the fixing plate with two (3x16") screws Ref Fig. 5.
- 23) Insert the Key in Lock Assembly and confirm its free rotation.
- 24) Remove key and Align the Notch Strip crank bush slot Fig. 6(a) & Square Rod slot Fig. 6(b) to the slot on cover plate. (back side of the lock).
- 25) Keep all Deadbolts inside the lock body.
- 26) Insert the Notch Strip & Square Rod through it's desired slot on crank bush of lock and fix the lock body to the door with 4 Nos. screws of (ø8x32mm) from front face of lock body Ref Fig. 7(L) & Fig. 7(R).
- 27) Ensure the smooth rotation of the key.

STRENGTHENING PLATE & RECEPTACLE FITMENT FOR INSIDE OPENING DOOR

FOR STRENGTHENING PLATE & RECEPTACLE FITMENT FOR INSIDE AS WELL AS OUTSIDE OPENING DOOR REFER PAGE NO. 17 & PAGE NO. 18

EUROPA
ANTI-THEFT ENGINEERING

FOR NON HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

HEXABOLT LOCK WITH LATCH BOLT (MODEL - H340, H342, H310, H312)
HEXABOLT LOCK WITHOUT LATCH BOLT (MODEL - H341, H349, H311, H319)

PREPARE THE DOOR

- 1) Confirm that door and frame surface are in same level

- 2) Place your Hexabolt lock body on the inside panel of the door at your desired height. (39" height from the floor recommended)
- 3) Mark the outline of the flap on the side face of the door with pencil, Ref Fig. 8(L) & Fig. 8(R).

- 4) Make 2mm deep recess of "158x21mm" on the marked area.
- 5) Once the recess is made ensure that the flap of your HEXABOLT lock remains flush with the surface of the door edge. (check it by keeping your HEXABOLT lock in the recess).
- 6) Fold the marker along the dotted line and place the shorter side of the marker in the recess.
- 7) Mark the hole centres A,B,C on the door panel with a pointed punch. Ref Fig. 9(L) & Fig. 9(R).
- 8) Now remove the marker and make 2 holes of Ø2.5x15mm deep at 2 locations of "C"
- 9) Make a Hole of Ø30mm throughout with hole saw cutter for Lock Assembly fitment at location "A".

EUROPA
ANTI-THEFT ENGINEERING

FOR NON HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

- 10) Make 7 holes of ø 3.5x25mm deep from inside of the door at location "B".

PROCEDURE FOR FITTING OF LOCK & KEY ASSEMBLY

- 11) Secure the fixing plate from inside of the door with (ø7x20mm) wood screws. Ref Fig. 10.
- 12) Insert lock assembly with cover ring from outside of the door. Ref Fig. 11.
- 13) Mark 8-10mm (max) on notch strip from the outer face of fixing plate from inside of door. Ref Fig. 12(b).

- 14) Insert screws of (3/16"x2") in to lock assembly and measure its extra length.
- 15) Remove the screw of (3/16"x2") and cut the extra length from its bottom side.
- 16) Cut the extra length of notch strip with Bolt Cutter. Ref Fig. 12(a).
- 17) Remove the burr over the screws of (3/16"x2") and notch strip with hand file. Ref Fig. 12(b).
- 18) Fix the lock assembly along with the fixing plate with 2 screws of (3/16") Ref Fig. 13.
- 19) Insert the key in lock assembly and confirm its free rotation.

EUROPA
ANTI-THEFT ENGINEERING

FOR NON HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

FITMENT OF LOCK BODY

- 20) Align the crank bush slot to the slot on cover plate. (back side of the lock) Ref Fig. 14
- 21) Keep all deadbolts inside the lock body.
- 22) Insert the projected notch strip through the slot on crank bush of lock and fix the lock body to the door with 4 Nos. screws of (Ø8x32mm) from flap side and 3 Nos. screw of (Ø8x55mm) from front face of lock body Ref Fig. 15
- 23) Ensure the smooth rotation of the key.

STRENGTHENING PLATE & RECEPTACLE FITMENT FOR HANDLE & NON HANDLE MODEL

- 24) Actuate the deadbolts out and insert the receptacle to the deadbolts.
- 25) Close the door to the door frame along with the receptacle and mark its outline on the frame. Ref Fig. 16(a).
- 26) Keep the receptacle top surface 2mm below the lock body top surface to prevent the lock operation tightness when the door will sag in future. (Make 2mm deep recess of "210mm x 32mm")
- 27) Mark all 5 Nos. screw centers (4 Nos. on side & 1 No. on front face) Ref Fig. 17.
- 28) Remove the receptacle & drill 5 holes (4 Nos. of Ø3.5x25mm & 1 No. of Ø3.5x55mm).

EUROPA
ANTI-THEFT ENGINEERING

FOR HANDLE & NON HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

- 29) Place the Strengthening plate on door frame by keeping flat face towards you and match the centre of the half circular cut on plate with centre hole on Receptacle (ø3.5x25mm approximately) Ref Fig. 17.

- 30) Mark 4 Nos. holes of the strengthening plate on the face of door frame. Drill the 4 holes with ø4mm drill up to 70mm depth. Then drill hole of ø5 up to 35 mm depth & fix the strengthening plate with 4 long screws Ref Fig. 18.
- 31) Screw up the Receptacle over the strengthening plate. Ref Fig. 19.

STRENGTHENING PLATE FIXING SCREW (ø5x75mm) 4Nos.

INSIDE MODEL INSTALLATION PROCEDURE IS SAME FOR WITH HANDLE & WITHOUT HANDLE MOEDLS

RECEPTACLE FITMENT FOR OUTSIDE OPENING DOOR

- 32) Keep the Receptacle over the fixed door frame and mark the outline of the Receptacle including the Deadbolt guiding holes & screw holes.
- 33) The marking of Receptacle to be done in such a way that the lock Deadbolt (already fitted over the door) has to match with the receptacle Deadbolt guiding holes for the proper functioning of lock after fitment.
- 34) Keep the Receptacle top surface 2mm below the lock body top surface to prevent the lock operation tightness when the door will sag in future.

EUROPA
ANTI-THEFT ENGINEERING

FOR HANDLE & NON HANDLE MODEL
INSTALLATION GUIDELINES & SETUP

- 35) Remove the Receptacle after marking and make a recess of 210x40x2mm and cavity for Dead bolts on the marked area over the wood frame.
- 36) Drill 3 Nos. screw holes of (ø3.5x25mm).
- 37) Screw up the Receptacle.

FINAL CHECKING OF LOCK OPERATION (FOR PLATE HANDLE MODELS)

- 1) Insert key, rotate and check whether the lock operates smoothly. The Deadbolts and the Latch bolt should slide smoothly in Receptacle. Also rotate the knob from inside and check whether the lock operates smoothly from inside.
- 2) The full round clockwise key rotation from outside of door makes the Deadbolts to go fully inside the lock body and again a quarter rotation makes the Latch to retract so that your door can be opened.
- 3) The anti-clockwise full round key rotation from outside door makes the Deadbolts to come fully outside the lock body so that your door is locked.

FINAL CHECKING OF LOCK OPERATION (FOR NON HANDLES MODELS)

- 1) Insert key, rotate it and check whether the lock operates smoothly. The dead bolt and the latch bolt should slide smoothly in receptacle. Also rotate the knob from inside and check whether the lock operates smoothly from inside.
- 2) The full round clockwise key rotation from outside of door make the deadbolts to go fully inside the lock body and again a quarter rotation makes the latch to retract so that your door can be opened.
- 3) The anti clock wise full round key rotation from outside door make the deadbolts to come fully outside the lock body so that your door is locked.

For periodic cleaning and lubrication of lock assembly use (zorrik88/wd40/csr/rustlick631)

EUROPA
ANTI-THEFT ENGINEERING

CONTACT DETAILS :

WELMADE LOCKING SYSTEMS PRIVATE LIMITED
J-61, MIDC, BHOSARI, PUNE - 411026. MAHARASHTRA (INDIA).
TOLL FREE NO. : 1800 123 061 061
TEL. : 020-27125012, FAX: 020-27126204
EMAIL : service@europalocks.com
VISIT US : www.europalocks.com

NOTE : KINDLY PRESERVE THIS CARD CAREFULLY
DURING RENOVATION (PAINTING/CONSTRUCTION WORK) COVER KEY HOLE OR CYLINDER BY ADHESIVE TAPE TO AVOID ENTRY OF DUST, FOREIGN PARTICLES INTO IT. DO NOT USE OIL IN LOCK ASSEMBLY FOR CLEANING USE OUR RECOMMENDED PRODUCT ZORRIK 88/WD40/RUSTLUCK 631.

- Images shown are for representation purpose, actual images may vary
- Specification may change in view of continuous development
- Imitation of label graphics is a punishable offence.
- *FFS available at selected serviceable area
- FFS not applicable for purchased through e-commerce platforms.

Thank You